## **TRAILER-WATT® 12S**



# The autonomous and mobile solar energy solution.

Transportable by light vehicles using the 12S solar trailer's ball hitch head, suspension, and self-braking.



#### Trailer-Watt® 12S technical specifications

#### Trailer dimensions and weight

Length (m)	6.40
Width (m)	2.30
Height (m)	1
Ground clearance (cm)	40
Weight (T)	1.5
Characteristics	Single axle, suspension, ball hitch head and self braking

#### Deployed photovoltaic solution

Length (m)	6.40
Width (m)	4.2
Height (m)	1
Maximum trailer slope	30°
Equipment for sloping	Manual hydrualic cylinder
Deployment time for one person	5 to 10 minutes

#### Photovoltaic system

Rigid monocrystalline
12 panels: 6 manually deployable and 6 fixed
400 Wp
4.8 kWp



5 kVA

#### **Conversion system**

Power

Output	Single-phase current (32A and 16A plug)
Batteries system	
Technology	LiFePO4, high stability with 4000 cycles of charge/discharge at 90% of DOD. Mobility certified
Storage nominal capacity	11.5 kWh (90% usable)
Voltage	48 V
Interfacing external energy sources	Possibility to connect on external diesel generator or on the grid
Operating temperature	-20° to 45° Battery charging temperature: 0°C to 45°C


#### **Options**

Lighting mast

#### **Applications**

Humanitarian, mobile construction sites, military, agriculture, rural electrification, mining, events, base camps, water and waste treatment.





- 1 Solar input
- 2 Charging inverter
- 3 Battery
- 4 AC box
- 5 DC box
- 6 MPPT Regulator
- 7 Output plug

- 8 Input plug
- 9 Generator dry contact plug
- 10 Ventilation
- Monitoring screen + 4G module
- 12 Emergency stop
- On / Off button

#### Trailer-Watt® 12S Advantages

- Plug & Play mobile solution on trailer
- Fast deployment (about 10 minutes)
- Chassis equipped with a pre-wired and pre-tested battery converter
- Specific batteries for mobile use
- Wiring according to European standards
- Safe and easy access for maintenance operation
- CE compliant products
- Made in France

### Examples of Realization: Trailer-Watt® 12S













